

Depending on each model we can offer further options:

Harddisk		2.5" Automotive-Harddisk for extreme operating conditions: <ul style="list-style-type: none"> • 24 hours / 7 days operation • -30 to +85° C operating temperature • extended shock and vibration strength
Solid-State-Memory		IDE Flash-Drive: "Industrial Grade", > 4 Mill. hours MTBF Compact-Flash: "Industrial Grade", > 2 Mill. read-write-cycles
Drives		DVD ROM, DVD writer, FDD
Power		DC power supply
Touchscreen		Resistiv or SAW, serial
Frontpanels incl. protection glass		<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>"Small" flush with housing</p> </div> <div style="text-align: center;"> <p>"Big" 3 mm steel sheet</p> </div> <div style="text-align: center;"> <p>19" 3 mm steel sheet</p> </div> <div style="text-align: center;"> <p>Panelmount 3 mm steel sheet</p> </div> </div> <div style="display: flex; justify-content: space-around; margin-top: 10px;"> <div style="text-align: center;"> <p>Panelmount 5 mm aluminium</p> </div> <div style="text-align: center;"> <p>Panelmount 10 mm aluminium</p> </div> <div style="text-align: center;"> <p>Panelmount operatorfront 5 mm aluminium</p> </div> <div style="text-align: center;"> <p>IP65 protection thanks to circular sealing lip with all aluminium panelmount frontbezels</p> </div> </div> <p>Detailed availabilities, dimensions and technical drawings you can easily find in the category "Frontpanel Overview" on our website www.tl-electronic.com</p>
IP65-protection all-around		<ul style="list-style-type: none"> • full protection against contact • absolutely dust-proof • protection against water jets in a rugged housing
		<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>full IP65 protection</p> </div> <div style="text-align: center;"> <p>Mounting sets</p> </div> <div style="text-align: center;"> <p>Stainless steel</p> </div> <div style="text-align: center;"> <p>Customised solutions</p> </div> </div>
VESA mounting accessories		<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;"> <p>Small Wallmount</p> </div> <div style="text-align: center;"> <p>Swing-Arm Wall</p> </div> <div style="text-align: center;"> <p>Swing-Arm Table</p> </div> </div>
Operating system		Windows® versions: NT, 2000, XP Professional, Server 2003, CE DOS 6.22, Linux, etc. with long term availability: e.g. Windows XP Professional – up to 2016
Software & Components		Ready-to-run System: <ul style="list-style-type: none"> • Installation of provided components, e.g. fieldbus cards • Installation of provided software or images
Tests		Also customer-specific test procedures 48 hours (instead of 24 hours) Burn-In stress test at constant 40° C Reports of all tests
Project support		Project support also on site / key account management
Shipping		Neutral OEM direct delivery, also to end customer Shock control during transport

Errors and changes excepted



TL Electronic GmbH
Bgm.-Gradl-Str. 1
85232 Bergkirchen-Feldgeding
Germany
Tel. / Fax +49 (0)8131 33204-0 / -150
www.tl-electronic.de

TL Electronic GmbH Österreich
Grazer Str. 10
8130 Frohnleiten
Austria
Tel. / Fax +43 (0)3126 51100-0 / -50
www.tl-electronic.at

TL Electronic GmbH Italy
Agency: MEBO srl
via Carso 18, 10141 Torino
Italy
Tel. / Fax +39 0173 610561
www.tl-electronic.it