



Order number: 23100657

Open text field 2: 10,4 Zoll (4:3) Panel-PC, Intel Celeron N6211

Manufacturer: Winmate

Weight: 7 kg

R10IE3S-GST2

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "R10IE3S-GST2"

Rugged Panel-PC für stationären und fahrzeugmontierten Einsatz
 Panel-Industrie-PC in robustem Stahlblech-Gehäuse
 Schutzart IP65 rundum inkl. Schnittstellen
 Schock- und vibrationsresistent gem. MIL-STD-810F/G
 Ebene PCAP-Glasfront ohne Schmutzkanten
 Ausgelegt für industrielle Anwendungen im Dauerbetrieb
 Einfache Installation mit rückseitiger VESA-Montageschnittstelle
 Langzeitverfügbarkeit

article group specification:	2310
Manufacturer:	WM
Manufacturer:	Winnate
series name:	GS-Serie
Manufacturer item number:	R10IE3S-GST2
mechanics:	Chassis (VESA-Mounting)
dimensions width:	25,24
dimensions height:	19,78
dimensions depth:	4,3
Material housing:	Stahlblech / steel sheet
protection device:	IP65
colour:	schwarz / black
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 75 x 75 mm, 100 x 100 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
cooling:	lüfterlos / fanless
Display-diagonal (inch):	10,4
aspect ratio:	4:3

resolution:	1024 x 768
brightness:	1000 cd/m ²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Projected Capacitive / Multi-Touch
Touch Interface:	USB
Manufacturer controller:	P-CAP Touchcontroller
voltage input DC:	9-36 V/DC (M12 type)
USB:	1 x USB 2.0 (M12 type)
serial:	1 x RS-232 (M12 type)
LAN:	1x RJ45 - 10/100/1000 Mbps (M12 type)
CPU Typ:	Celeron
CPU Model:	N6211
CPU 64bit:	Ja
CPU speed:	1,2 GHz
CPU cores:	2
CPU socket:	FCBGA1493
RAM size (MB):	8192
RAM max. size (MB):	16384
Grafik Controller:	Intel UHD Graphics for 10th Generation
safety:	TPM 2.0
SSD capacity (GB):	128
Ethernet connections:	1x LAN - 10/100/1000 Mbps
Ethernet data transfer:	1 x Gigabit-LAN
Ethernet Controller :	1 x Intel Gigabit Ethernet Controller
Betriebssystem:	Optional
operating-system language version:	deutsch / english / italian
operating temperatur min.:	-15°C
operating temperatur max.:	55°C
warranty:	24 Monate / 24 months

Related links to "R10IE3S-GST2"

- [- Do you have any questions concerning this product?](#)
- [- Further products by Winmate](#)

Available downloads:

[Download Drawing Panel-PC R10IE3S-GST2 260523.pdf](#)