

Order number: 23120473
Open text field 2: 12,1 Zoll (4:3) Panel-PC, Intel Celeron N6211
Manufacturer: Winmate

R12IE3S-GSM2

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "R12IE3S-GSM2"

Rugged Panel PC for stationary and vehicle-mounted use Industrial Panel PC in sturdy steel sheet housing Protection class IP65 all around incl. Interfaces Shock and vibration resistant acc. MIL-STD-810F/G Flat PCAP glass front without dirt-collecting edges Designed for industrial applications in continuous operation Easy installation with rear VESA mounting interface Long-term availability

article group specification:	2312
Manufacturer:	WM
Manufacturer:	Winmate
series name:	GS-Serie
Manufacturer item number:	R12IE3S-GSM2
mechanics:	Chassis (VESA-Mounting)
dimensions width:	29,62
dimensions height:	22,67
dimensions depth:	4,55
Material housing:	Aluminium / aluminium
protection device:	IP65
colour:	schwarz / black
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 75 x 75 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
cooling:	lüfterlos / fanless
Display-diagonal (inch):	12,1
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	500 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Touch-Screen or glass:	Projected Capactive / Multi-Touch
Touch Interface:	USB
Manufacturer controller:	P-CAP Touchcontroller
voltage input DC:	9-36 V/DC (M12 type)
external power supply:	12 V/DC, 100 - 240 V/AC, DC plug
USB:	1 x USB 2.0 (M12 type)
serial:	1 x RS-232 (M12 type)
LAN:	1x LAN - 10/100/1000 Mbps (M12 type)
CPU Typ:	Celeron
CPU Model:	N6211
CPU 64bit:	Ja
CPU speed:	1,2 GHz
CPU cores:	2
CPU socket:	FCBGA1493
RAM size (MB):	8192
RAM max. size (MB):	16384
Grafik Controller:	Intel UHD Graphics for 10th Generation
safety:	TPM 2.0
SSD capacity (GB):	128
Ethernet connections:	1x LAN - 10/100/1000 Mbps
Ethernet data transfer:	1 x Gigabit-LAN
Ethernet Controller :	1 x Intel Gigabit Ethernet Controller
Betriebssystem:	Optional
operating-system language version:	deutsch / english / italian
operating temperatur min.:	-15°C
operating temperatur max.:	55°C
warranty:	24 Monate / 24 months

Related links to "R12IE3S-GSM2"

- Do you have any questions concerning this product?
- Further products by Winmate

Available downloads:

Download Drawing Panel-PC R12IE3S-GSM2 260529.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de