



Order number: 23120473

Open text field 2: 12,1 Zoll (4:3) Panel-PC, Intel Celeron N6211

Manufacturer: Winmate

R12IE3S-GSM2

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "R12IE3S-GSM2"

Rugged Panel PC for stationary and vehicle-mounted use Industrial Panel PC in sturdy steel sheet housing Protection class IP65 all around incl. Interfaces Shock and vibration resistant acc. MIL-STD-810F/G Flat PCAP glass front without dirt-collecting edges Designed for industrial applications in continuous operation Easy installation with rear VESA mounting interface Long-term availability

| | |
|------------------------------|--|
| article group specification: | 2312 |
| Manufacturer: | WM |
| Manufacturer: | Winnate |
| series name: | GS-Serie |
| Manufacturer item number: | R12IE3S-GSM2 |
| mechanics: | Chassis (VESA-Mounting) |
| dimensions width: | 29,62 |
| dimensions height: | 22,67 |
| dimensions depth: | 4,55 |
| Material housing: | Aluminium / aluminium |
| protection device: | IP65 |
| colour: | schwarz / black |
| controls: | 2 Keys: Power, Reset |
| VESA-Mounting Interface: | VESA 75 x 75 mm |
| mounting: | Tragarm-, Standfuß-, Wandmontage / Suppo |
| cooling: | lüfterlos / fanless |
| Display-diagonal (inch): | 12,1 |
| aspect ratio: | 4:3 |
| resolution: | 1024 x 768 |
| brightness: | 500 cd/m ² |
| contrast: | 1000:1 |
| Display-Technology: | LCD, LED Backlight |

| | |
|---|--|
| Touch-Screen or glass: | Projected Capacitive / Multi-Touch |
| Touch Interface: | USB |
| Manufacturer controller: | P-CAP Touchcontroller |
| voltage input DC: | 9-36 V/DC (M12 type) |
| external power supply: | 12 V/DC, 100 - 240 V/AC, DC plug |
| USB: | 1 x USB 2.0 (M12 type) |
| serial: | 1 x RS-232 (M12 type) |
| LAN: | 1x LAN - 10/100/1000 Mbps (M12 type) |
| CPU Typ: | Celeron |
| CPU Model: | N6211 |
| CPU 64bit: | Ja |
| CPU speed: | 1,2 GHz |
| CPU cores: | 2 |
| CPU socket: | FCBGA1493 |
| RAM size (MB): | 8192 |
| RAM max. size (MB): | 16384 |
| Grafik Controller: | Intel UHD Graphics for 10th Generation |
| safety: | TPM 2.0 |
| SSD capacity (GB): | 128 |
| Ethernet connections: | 1x LAN - 10/100/1000 Mbps |
| Ethernet data transfer: | 1 x Gigabit-LAN |
| Ethernet Controller : | 1 x Intel Gigabit Ethernet Controller |
| Betriebssystem: | Optional |
| operating-system language version: | deutsch / english / italian |
| operating temperatur min.: | -15°C |
| operating temperatur max.: | 55°C |
| warranty: | 24 Monate / 24 months |

Related links to "R12IE3S-GSM2"

- [Do you have any questions concerning this product?](#)
- [Further products by Winmate](#)

Available downloads:

[Download Drawing Panel-PC R12IE3S-GSM2 260529.pdf](#)