

Order number: 23152691
Open text field 2: 15,0 Zoll (4:3) Panel-PC, Intel Pentium N4200
Manufacturer: TL Electronic, Bergkirchen-Feldgeding
Weight:6.3 kg

R15IP7T-OFC3_19

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "R15IP7T-OFC3_19"

Built-in Panel PC for professional use Industrial Panel PC in sturdy steel sheet design Robust steel sheet front panel (IP65 protected) Designed for industrial applications in continuous operation Ready to install for the 19-inch rack Long-term availability

article group specification:	2315
Manufacturer:	WM
Manufacturer:	Winmate
series name:	SlimLine-Serie
Manufacturer item number:	R15IPT-OFC3
mechanics:	19" Rack Mount
dimensions width:	48,3
dimensions height:	35,48
dimensions depth:	6,6
weight:	6,3
Material housing:	Stahlblech / steel sheet
Material Front :	Stahlblech / steel sheet
protection front:	IP65
protection device:	IP20
colour:	RAL 7035 / light grey
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 75 x 75 mm, 100 x 100 mm
mounting:	Einbau von vorne / front installation
cooling:	lüfterlos / fanless
Display-diagonal (inch):	15,0
aspect ratio:	4:3
resolution:	1024 x 768

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

brightness:	300 cd/m²
contrast:	2000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Resistive / Glas (optional)
Touch Interface:	USB
Manufacturer controller:	Premier
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, DC plug
VGA:	1 x VGA (optional)
HDMI:	1 x HDMI 1.4 (optional)
DisplayPort:	1 x DP 1.2
USB:	4 x USB 3.2 Gen.1x1 (Type-A)
serial:	2 x RS232
Audio:	1 x Mic-In, 1 x Line-Out, 2 x Speaker
LAN:	2x Giga LAN RJ45
CPU Typ:	Pentium 4
CPU Model:	N4200
CPU 64bit:	Ja
CPU speed:	1,1 GHz
CPU cores:	4
CPU socket:	FCBGA1296
RAM size (MB):	8192
RAM max. size (MB):	16384
Grafik Controller:	Intel HD Graphics 505
safety:	TPM 2.0
SSD capacity (GB):	128
Ethernet connections:	2 x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Ethernet Controller :	2 x Intel Ethernet Controller
WLAN :	Optional / optional
Bluetooth :	optional / optional
Betriebssystem:	Optional
operating-system language version:	deutsch / english / italian
operating temperatur min.:	0°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Related links to "R15IP7T-OFC3_19"

- Do you have any questions concerning this product?
- Further products by TL Electronic, Bergkirchen-Feldgeding

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Available downloads:

Download Drawing (19-inch Rackmount) Installation 260805.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de