



Order number: 23171506

Open text field 2: 17,0 Zoll (4:3) Panel-PC der SlimLine-Serie, Intel Celeron N2930

Manufacturer: TL Electronic, Bergkirchen-Feldgeding

WM 17-IB70-PME-GS

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "WM 17-IB70-PME-GS"

Industrial LCD for professional use Industrial monitor in sturdy steel sheet design Robust stainless steel front panel (IP65 protected) Designed for industrial applications in continuous operation Panelmount installation with rear screwed bolts Long-term availability

article group specification:	2317
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	WM-Serie
Manufacturer item number:	R17IB7T-OFM1
mechanics:	Panel Mount Edelstahl / stainless steel
dimensions width:	48,3
dimensions height:	39,9
dimensions depth:	8,8
Material housing:	Stahlblech / steel sheet
Material Front :	Edelstahl / stainless steel
protection front:	IP65
protection device:	IP20
colour:	Edelstahl gebürstet / brushed stainless steel
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 75 x 75 mm, 100 x 100 mm
mounting:	Einbau von vorne / front installation
cooling:	lüfterlos / fanless
Display-diagonal (inch):	17
aspect ratio:	4:3
resolution:	1280 x 1024

brightness:	350 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Schutzglas / protective glass
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, 4-pin
input:	65 Watt
VGA:	1 x 15-pin D-sub
USB:	1 x USB 3.0, 3 x USB 2.0
serial:	1 x RS-232, 1 x RS232/422/485
Audio:	Line-Out, Line-In, Mic in
LAN:	2x RJ45 - 10/100/1000 Mbps
PS/2:	2x Mini-DIN
Mainboard form factor:	Mini-ITX
chipset:	Intel System on chip
CPU Typ:	Celeron Bay Trail-M
CPU Model:	N2930
CPU 64bit:	Ja
CPU speed:	1,83 GHz
CPU cores:	4
CPU socket:	FCBGA1170
RAM size (MB):	4096
RAM max. size (MB):	8192
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1600
Grafik Controller:	Intel HD Graphics Engine
Audio Controller:	Realtek ALC886 HD Codec
safety:	TPM 1.2
connections SATA:	1
CPU class:	Atom / Celeron
SSD design:	2.5"
SSD capacity (GB):	128
Ethernet connections:	2 x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Ethernet Controller :	Intel I210-AT
MiniPCle Slot WLAN/WWAN :	1
Betriebssystem:	Optional
operating-system support:	Windows 7 / 8.1 / 10 IoT
operating temperatur min.:	0°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Related links to "WM 17-IB70-PME-GS"

- [Do you have any questions concerning this product?](#)
- [Further products by TL Electronic, Bergkirchen-Feldgeding](#)

Available downloads:

- [Download CE Konformitätserklärung DoC Panel-PC WM 17-IB70-x-y-z 20190130](#)
- [Download Drawing WM 17-...-PMA+PME \(Panelmount\) Installation 190228](#)
- [Download Drawing Panel-PC WM 17-...-PMA+PME \(Panelmount\) 190228](#)
- [Download CE Panel-PC WM-Serie Gebrauchsanleitung 20190130](#)