

Order number: 15000486
Open text field 2: Embedded Industrie-PC der EmbeddedLine-Serie (EL10
Manufacturer: Protech
Weight:2 kg

EL1083

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "EL1083"

Booksize Embedded PC for professional use Industrial computer in sturdy aluminium housing Designed for industrial applications in continuous operation Easy installation with mounting bars or DIN Rail kit Long-term availability

article group specification:	150
Manufacturer:	PT
Matchcode manufacturer:	nein
Manufacturer:	Protech
series name:	EmbeddedLine
Manufacturer item number:	SE-8124
mechanics:	Embedded-PC
dimensions width:	21,7
dimensions height:	4,5
dimensions depth:	14,8
weight:	2,0
Material housing:	Aluminium und Stahlblech / aluminium and steel sheet
Material Front :	Stahlblech / steel sheet
protection front:	IP20
protection device:	IP20
colour:	schwarz / black
controls:	2 Keys: Power, Reset, Status-LEDs
VESA-Mounting Interface:	Nein / no
wall mounting:	Optional / optional
DIN-Rail:	Optional / optional
cooling:	lüfterlos / fanless
chipset:	Intel System on chip

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

CPU Typ :	Celeron Bay Trail-M
CPU Model :	J1900
CPU 64bit :	Ja
CPU speed:	2000
CPU cores:	4
RAM size (MB):	4096
RAM max. size (MB):	8192
RAM Number of benches:	1
RAM Typ :	SO-DDR3L
RAM speed:	1600
Grafik Controller:	Intel HD Graphics Z3700 series
Ethernet Controller:	Intel I210IT
Audio Controller:	Realtek ALC888S HD Codec
connections SATA:	1
Mini-PCIe-slot:	2
HDD design:	2.5"
HDD max. number:	1
HDD connection:	SATA
HDD capacity (GB):	500
MiniPCIe Slot SSD :	1
RAID-System :	Nein / no
alternate Caddies:	Nein / no
CD/DVD-Writer :	Nein / no
Display:	1x DVI-D
USB :	1 x USB 2.0
Seriell :	2 x RS-232
SD Card Slot :	Ja / yes
Digitale I/O :	1 x 4in / 4out
controls:	Kontroll-LEDs
Display :	1x DVI-I
USB :	1 x USB 3.0, 1 x USB 2.0
LAN :	2x RJ45 - 10/100/1000 Mbps
Audio :	Line-Out, Line-In, Mic in
serial:	2 x RS232/422/485
controls:	Power On/Off, Reset
voltage input DC:	9-36 V/DC
power adapter:	Optional externes Netzteil 100 - 240 V/AC
WLAN:	Optional / optional
GSM :	Optional / optional
GPS :	Optional / optional
operating-system support:	Windows 7 / 8.1 / 10 IoT
operating temperatur min.:	0°C

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

operating temperatur min.:	45°C
warranty:	24 Monate / 24 months

Related links to "EL1083"

- Do you have any questions concerning this product?
- Further products by Protech

Available downloads:

Download PT Quick Guide EL1083 v.Q1
Download PT User Manual EL1083 v.3.0
Download CE_Embedded-Industrie-PC EL1083 Gebrauchsanleitung 20190130
Download CE Konformitätserklärung DoC IPC EL1083_20190130
Download Drawing Embedded-Industrie-PC EL1083(-EC) 190228
Download Drawing Embedded-Industrie-PC EL1083(-EC) + Wall Mount Side Brackets 230517.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de