

Order number: 23152152
Open text field 2: 15,0 Zoll (4:3) Rugged Panel-PC der GS-Serie, Intel Celeron N2930
Manufacturer: TL Electronic
Weight:6 kg

R15IB3S-GSC3

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "R15IB3S-GSC3"

Rugged Panel PC for stationary and vehicle-mounted use Industrial Panel PC in sturdy steel sheet housing Protection class IP65 all around incl. Interfaces Shock and vibration resistant acc. MIL-STD-810F/G Flat PCAP glass front without dirt-collecting edges Designed for industrial applications in continuous operation Easy installation with rear VESA mounting interface Long-term availability

article group specification:	2315
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	GS-Serie
Manufacturer item number:	R15IB3S-GSC3
mechanics:	Chassis (VESA-Mounting)
dimensions width:	36,34
dimensions height:	27,79
dimensions depth:	0,52
Material housing:	Stahlblech / steel sheet
Material Front :	Stahlblech / steel sheet
protection front:	IP65
protection device:	IP65
colour:	RAL 9004 / signal black
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 100 x 100 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Support arm, stand, wall mount
cooling:	lüfterlos / fanless
Display-diagonal (inch):	15
aspect ratio:	4:3
resolution:	1024 x 768

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

brightness:	250 cd/m²
contrast:	700:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Projected Capactive / Multi-Touch
Touch Interface:	USB
Manufacturer controller:	P-CAP Touchcontroller
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, IP65
input:	25 Watt
USB:	1 x USB 2.0 (M12 type)
serial:	1 x RS232 (M12 type) (Optional 422/485)
Audio:	1 x 1 Watt Speaker
LAN:	1x RJ45 - 10/100/1000 Mbps (M12 type)
Mainboard form factor:	3,5"
chipset:	Intel System on chip
CPU Typ:	Celeron Bay Trail-M
CPU Model:	N2930
CPU 64bit:	Ja
CPU speed:	1,83 GHz
CPU cores:	1
CPU socket:	CPU Onboard
RAM size (MB):	4096
RAM max. size (MB):	8192
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1600
Grafik Controller:	Graphics in CPU
Audio Controller:	Realtek ALC886 HD Codec
safety:	TPM 1.2
connections SATA:	1
CPU class:	Atom / Celeron
SSD design:	mSATA
SSD capacity (GB):	128
RAID-System:	Nein / no
CD/DVD-Writer :	Nein / no
Ethernet Controller :	Intel I210-AT
WLAN :	Nein / no
Bluetooth :	Nein / no
camera:	Nein / no
Barcode Scanner:	Nein / no
RFID Reader :	Nein / no
Betriebssystem:	Optional

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

operating-system language version:	deutsch / english / italian
operating-system support:	Windows 7 / 8.1 / 10 IoT
operating temperatur min.:	0°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Related links to "R15IB3S-GSC3"

- Do you have any questions concerning this product?
- Further products by TL Electronic

Available downloads:

Download Drawing Panel-PC R15IB3S-GSC3 190228

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de