



Order number: 23120394

Open text field 2: 12,1 Zoll (4:3) Panel-PC, Intel Celeron N2930

Manufacturer: TL Electronic

Weight: 6 kg

R12IB3S-OFM2_PMA

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "R12IB3S-OFM2_PMA"

Built-in Panel PC for professional use Industrial Panel PC in sturdy steel sheet design Robust aluminium front panel (IP65 protected) Designed for industrial applications in continuous operation Panelmount installation with rear screwed bolts Long-term availability

article group specification:	2312
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	SlimLine-Serie
Manufacturer item number:	R12IB3S-OFM2
mechanics:	Panel Mount
dimensions width:	34
dimensions height:	29
dimensions depth:	4,3
Material housing:	Stahlblech / steel sheet
Material Front :	Aluminium / aluminum
protection front:	IP65
protection device:	IP22
colour:	RAL 7035 / light grey
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 75 x 75 mm
mounting:	Einbau von vorne / front installation
cooling:	lüfterlos / fanless
Display-diagonal (inch):	12,1
aspect ratio:	4:3
resolution:	800 x 600

brightness:	450 cd/m²
contrast:	700:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Resistive / Glas (optional)
Touch Interface:	USB oder RS-232
Manufacturer controller:	Premier
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, 4-pin
input:	15 Watt
VGA:	1 x 15-pin D-sub
DVI:	1 x DVI-I
HDMI:	1 x HDMI (Type-A)
DisplayPort:	1 x DisplayPort
Video:	1 x Composite (PAL / NTSC)
serial:	1 x RS-232, 1 x RS232/422/485
Audio:	Line-Out, Line-In, Mic in
LAN:	1x RJ45 - 10/100/1000 Mbps (IP65)
PS/2:	2x Mini-DIN
Mainboard form factor:	3,5"
chipset:	Intel System on chip
CPU Typ:	Celeron Bay Trail-M
CPU Model:	N2930
CPU 64bit:	Ja
CPU speed:	1,8 GHz
CPU cores:	4
CPU socket:	LGA1150, H3
RAM max. size (MB):	8192
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1066
Grafik Controller:	Graphics in CPU
Audio Controller:	Realtek ALC886 HD Codec
safety:	TPM 2.0
CPU class:	Atom / Celeron
HDD max. number:	1
HDD connection:	SATA
HDD capacity (GB):	500
RAID-System:	Nein / no
CD/DVD-Writer :	Nein / no
Ethernet connections:	2 x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
MiniPCIe Slot WLAN/WWAN :	1

WLAN :	Ja / yes
Bluetooth :	Nein / no
camera:	Nein / no
Barcode Scanner:	Nein / no
RFID Reader :	Nein / no
Betriebssystem:	Windows 10 IoT Enterprise / Windows Embedded 8 / Windows Embedded 7
operating-system language version:	deutsch / english / italian
operating-system support:	Windows 10 IoT
operating temperatur min.:	0°C
operating temperatur max.:	55°C
warranty:	24 Monate / 24 months

Related links to "R12IB3S-OFM2_PMA"

- [- Do you have any questions concerning this product?](#)
- [- Further products by TL Electronic](#)

Available downloads:

- [Download CE Konformitätserklärung DoC Panel-PC WM 12-IB32-x-y-z 20190130](#)
- [Download Drawing Panel-PC WM 12-IB32-PMA+PME \(Panelmount\) 190228](#)
- [Download CE Panel-PC WM-Serie Gebrauchsanleitung 20190130](#)