



**Order number:** 15100431

**Open text field 2:** Wallmount Industrie-PC der EmbeddedLine-Serie (SE-

**Manufacturer:** Protech

**Weight:** 4.9 kg

## EmbeddedLine EL1092-Q

### Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

### Product information "EmbeddedLine EL1092-Q"

Booksize Industrial PC for professional use Industrial computer in sturdy aluminium housing 2 x drive bays, RAID option Designed for industrial applications in continuous operation Easy installation with mounting bars Long-term availability

|                              |                                   |
|------------------------------|-----------------------------------|
| article group specification: | 151                               |
| Manufacturer:                | PT                                |
| Matchcode manufacturer:      | nein                              |
| Manufacturer:                | Protech                           |
| series name:                 | EmbeddedLine                      |
| Manufacturer item number:    | SE-8400                           |
| mechanics:                   | Embedded-PC                       |
| dimensions width:            | 26,0                              |
| dimensions height:           | 8,0                               |
| dimensions depth:            | 20,0                              |
| weight:                      | 4,9                               |
| Material housing:            | Aluminium / aluminium             |
| Material Front :             | Aluminium / aluminum              |
| protection front:            | IP20                              |
| protection device:           | IP20                              |
| colour:                      | Gehäuse schwarz / Front blau      |
| controls:                    | 2 Keys: Power, Reset, Status-LEDs |
| wall mounting:               | Optional / optional               |
| cooling:                     | lüfterlos / fanless               |
| chipset:                     | Intel Q170                        |
| CPU Typ :                    | Core i3                           |
| CPU Model :                  | 7100T                             |

|                              |                                          |
|------------------------------|------------------------------------------|
| CPU 64bit :                  | Ja                                       |
| CPU speed:                   | 3400                                     |
| CPU cores:                   | 2                                        |
| CPU socket:                  | LGA1151, H4                              |
| CPU alternative option 1:    | Core i5-7xxx                             |
| CPU alternative option 2:    | Core i7-7xxx                             |
| CPU alternative option 3:    | Core i5-6xxx                             |
| RAM size (MB):               | 8192                                     |
| RAM max. size (MB):          | 32768                                    |
| RAM Number of benches:       | 2                                        |
| RAM Typ :                    | DDR4                                     |
| RAM speed:                   | 2133                                     |
| PCI Express x4 :             | Optional / optional                      |
| PCI :                        | Optional / optional                      |
| Grafik Controller:           | Intel HD Graphics 630                    |
| Ethernet Controller:         | Intel PHY219-LM + 210-AT                 |
| connections SATA:            | 2                                        |
| USB internal connections:    | 4x USB 2.0, 2x USB 3.0                   |
| Connections Serial internal: | 4x RS-232                                |
| Mini-PCIe-slot:              | 1                                        |
| SSD design:                  | 2.5"                                     |
| SSD max. number:             | 2                                        |
| SSD capacity (GB):           | 120                                      |
| RAID-System :                | Ja / yes                                 |
| Display:                     | 1x HDMI                                  |
| USB :                        | 2 x USB 3.0                              |
| Seriell :                    | 2 x RS-232                               |
| SIM Card Slot :              | Ja / yes                                 |
| Cfast Card Slot :            | Ja / yes                                 |
| Display :                    | 1x DVI-I                                 |
| USB :                        | 4 x USB 3.0                              |
| LAN :                        | 2x RJ45 - 10/100/1000 Mbps               |
| Audio :                      | Line-Out, Line-In, Mic in                |
| serial:                      | 2 x RS-232, 2 x RS232/422/485            |
| controls:                    | Power On/Off                             |
| voltage input DC:            | 9-36 V/DC                                |
| power adapter:               | Optional externes Netzteil 100 - 240 V/A |
| WLAN:                        | Optional / optional                      |
| operating-system support:    | Windows 7 / 8.1 / 10 IoT                 |
| operating temperatur min.:   | -10°C                                    |
| operating temperatur min.:   | 50°C                                     |
| warranty:                    | 24 Monate / 24 months                    |

## Related links to "EmbeddedLine EL1092-Q"

- [Do you have any questions concerning this product?](#)
- [Further products by Protech](#)

## Available downloads:

- [Download CE Konformitätserklärung DoC IPC EL1092\\_20190130](#)
- [Download Drawing Embedded-Industrie-PC EL1092\\_190228](#)
- [Download Gebrauchsanleitung IPC-EL1092-1093\\_20190130](#)
- [Download PT EL1092 Quick Reference Guide Q1](#)
- [Download PT EL1092 README V1.0](#)
- [Download PT EL1092 User Manual M1\\_190228](#)
- [Download Drawing Embedded-Industrie-PC EL1092\\_pci\\_20200731](#)
- [Download Drawing Embedded-Industrie-PC EL1092\\_pci-e\\_20200731](#)