



Order number: 25070001

Open text field 2: 7,0 Zoll (16:9), Intel Celeron N3350, Windows 10 IoT Enterprise

Manufacturer: Winmate

Weight: 1 kg

FM07

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "FM07"

Tablet PC ready for vehicle and forklift installation Ruggedized Tablet and docking unit in sturdy magnesium alloy housing Protection class IP65 all around incl. Interfaces Shock and vibration protected (MIL-STD-810G) Antiscratch resistive touch (finger & stylus) The ideal partner for warehouse, logistics, automotive, outdoor etc. Long-term availability

article group specification:	2307
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
series name:	Vehicle Mounted Computer
Manufacturer item number:	FM07
mechanics:	Vehicle Mount Computer
dimensions width:	19,0
dimensions height:	14,6
dimensions depth:	4
weight:	1
Material housing:	Aluminium / aluminium
colour:	Schwarz / black
VESA-Mounting Interface:	VESA 75 x 75
cooling:	l�fterlos / fanless
Display-diagonal (inch):	7
aspect ratio:	16:9
resolution:	1024 x 600
brightness:	1000 cd/m ²
contrast:	700:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch

usability:	Finger/Stift / finger/pen
CPU Typ:	Intel Celeron
CPU Model:	N3350
CPU speed:	1,1 GHz
CPU cores:	2
RAM size (MB):	2048
RAM max. Größe (MB):	8192
RAM Typ:	SO-DDR3L
RAM speed:	1600
SSD design:	M.2
SSD capacity:	128
SSD number:	1
SSD number max.:	1
RAID-System:	Nein / no
WLAN:	Ja / yes
WLAN-Standard:	IEEE 802.11 a/b/g/n/ac
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Nein / no
Camera rear:	Nein / no
Barcode:	Nein / no
RFID:	Nein / no
Finger Print:	Nein / no
USB:	2x 3.0 USB (Type A)
serial:	1x RS-232
LAN:	1x RJ45 - 10/100/1000 Mbps
Card Slot:	1x SD Slot
Audio:	Canbus
Power:	1x 9-36 V/DC, DC plug
controls:	7 Keys: Power, 6x Function
operating system:	Windows 10 IoT Enterprise
operating system optional:	Ubuntu
operating temperatur min.:	-20°C
operating temperatur max.:	60°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
voltage input DC:	12-19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery Hot-Swap:	Nein / no

Related links to "FM07"

- [Do you have any questions concerning this product?](#)
- [Further products by Winmate](#)

Available downloads:

- [Download Drawing Vehicle Mounted Computer FM07 221212.pdf](#)
- [Download CE Konformitätserklärung DoC FM07.pdf](#)