



Order number: 52200758

Open text field 2: 21,5 Zoll (16:9) Multitouch-Monitor

Manufacturer: TL Electronic, Bergkirchen-Feldgeding

W22L100-SPA369

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "W22L100-SPA369"

Robust industrial monitor made of brushed stainless steel Protection class IP69K all around incl. interfaces Easy to clean and corrosion resistant Designed for industrial applications in continuous operation Easy installation with rear VESA mounting interface Perfect for food, chemical, pharmaceutical industry, medical technology, process engineering, plant construction etc. Long-term availability 21,5" (16:9) LCD in robust Flat Stainless Steel Housing Gehäusematerial: SUS 316 / AISI 316 stainless steel Protection class: IP69K Abmaße: 541 x 337 x 56.2 mm Resolution: 1920 x 1080 Pixel Contrast: 3000:1 Brightness: 250 cd/m² Viewing angle: Hor.: -89° to 89°, Vert.: -89° to 89° Videoeingang: 15 pin HD Sub Buchse (VGA) + HDMI (incl. IP67-geschützten Kabel) Versorgungsspannung: 12 V/DC über externes Netzteil mit 100-240 V/AC With rear VESA Mounting (200x100 mm) incl. projected capacitive Multi-Touchscreen (PCAP) Type: W22L100-SPA369 Operating temperature: 0° to 45° C Country of origin: Taiwan

article group specification:	522
Manufacturer:	WM
Manufacturer:	Winmate
series name:	ES-Serie
Manufacturer item number:	W22L100-SPA369
mechanics:	Chassis Edelstahl / stainless steel (VES
dimensions width:	54,1
dimensions height:	33,7
dimensions depth:	5,62
Material Front :	Edelstahl / stainless steel
protection front:	IP69K
protection device:	IP69K
colour:	Edelstahl gebürstet / brushed stainless
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 200 x 100 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
Display-diagonal (inch):	21,5
aspect ratio:	16:9

resolution:	1920 x 1080
brightness:	250 cd/m²
contrast:	3000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Projected Capacitive / Multi-Touch
Touch Interface:	USB
Manufacturer controller:	P-CAP Touchcontroller
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, IP65
input:	50 Watt
VGA:	1 x 12-pin (IP65)
DVI:	1 x DVI (optional)
USB:	1 x USB 2.0 (M12 type)
operating temperatur min.:	-10°C
operating temperatur max.:	55°C
warranty:	24 Monate / 24 months

Related links to "W22L100-SPA369"

- [- Do you have any questions concerning this product?](#)
- [- Further products by TL Electronic, Bergkirchen-Feldgeding](#)

Available downloads:

- [Download CE Konformitätserklärung DoC LCD WM 22W-Vu-x-y-z 20190130](#)
- [Download CE Industrie-LCD WM-Serie Gebrauchsanleitung 20190130](#)
- [Download Drawing Industrie-LCD WM 22W-V-69K-ES-MTU 221219](#)