


Order number: 23152341

Open text field 2: 15,0 Zoll (4:3) Panel-PC, Intel Celeron N2930

Manufacturer: TL Electronic

Weight: 11 kg

R15IB7T-OFC3_PCA

Price on request

 Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "R15IB7T-OFC3_PCA"

Robust industrial Panel PC with all-round protection Rugged housing made of powder-coated aluminium profiles Protection class IP65 all around incl. interfaces Designed for industrial applications in continuous operation Installation through various mounting sets (optional) with internal cable routing Long-term availability

article group specification:	2315
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	TL Electronic
series name:	ControlLine-Serie
mechanics:	Rugged Panel-PC
dimensions width:	47,1
dimensions height:	39,6
dimensions depth:	12
weight:	11
Material housing:	Aluminium / aluminium
Material Front :	Aluminium / aluminum
protection front:	IP65
protection device:	IP65
colour:	RAL 7035 / Eckprofile RAL 5010
controls:	2 Keys: Power, Reset, Status-LEDs
VESA-Mounting Interface:	Optional / optional
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
Display-diagonal (inch):	15,0
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	250 cd/m²

contrast:	500:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Resistive / Glas (optional)
Touch Interface:	USB oder RS-232
Manufacturer controller:	Premier
voltage input AC:	100 - 240 V/AC
input:	30 Watt
VGA:	1 x 15-pin D-sub
USB:	1 x USB 3.0, 3 x USB 2.0
serial:	2 x RS-232, 1 x RS232/422/485
Audio:	Line-Out, Line-In, Mic in
LAN:	2x RJ45 - 10/100/1000 Mbps
PS/2:	2x Mini-DIN
chipset:	Intel System on chip
CPU Typ:	Celeron Bay Trail-M
CPU Model:	N2930
CPU 64bit:	Ja
CPU speed:	1,83 GHz
CPU cores:	4
CPU socket:	CPU on Board
RAM size (MB):	4096
RAM max. size (MB):	8192
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1600
Grafik Controller:	Intel HD Graphics Z3700 series
Audio Controller:	Realtek ALC886 HD Codec
safety:	TPM 1.2
connections SATA:	1
CPU class:	Atom / Celeron
SSD design:	2.5"
SSD max. number:	1
SSD capacity (GB):	128
Ethernet connections:	2 x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Ethernet Controller :	Intel I210-AT
MiniPCle Slot WLAN/WWAN :	1
WLAN :	Optional / optional
operating-system support:	Windows 7 / 8.1 / 10 IoT
operating temperatur min.:	0°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Related links to "R15IB7T-OFC3_PCA"

- [Do you have any questions concerning this product?](#)
- [Further products by TL Electronic](#)

Available downloads:

- [Download CE Konformitätserklärung DoC PPC ControlLine WM 15-IB70-x-y-z 20122020](#)
- [Download Drawing Panel-PC WM 15-IB70-PCA \(IP65\) 190228](#)
- [Download CE Panel-PC WM-Serie Gebrauchsanleitung 20190130](#)