



Order number: 25130026

Open text field 2: 11,6 Zoll (16:9) Rugged Industrie-Tablet-PC, Intel Pentium N4200, Windows 10 IoT Enterprise

Manufacturer: Winmate

Weight: 1.4 kg

M116P

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "M116P"

Tablet PC for professional use Ruggedized Tablet in sturdy aluminium housing Protection class IP65 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810G) Multi-touch (PCAP) with Glove / Rain / Stylus modes Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc.

article group specification:	2513
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M116
mechanics:	Rugged Tablet PC
dimensions width:	30,06
dimensions height:	20,2
dimensions depth:	2,25
weight:	1,4
Material housing:	Aluminium - Magnesium
protection device:	IP65
colour:	Schwarz / black
cooling:	lüfterlos / fanless
Display-diagonal (inch):	11,6
aspect ratio:	16:9
resolution:	1920 x 1080
brightness:	850 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight

Touch-Screen :	Projected Capacitive / Multi-Touch
usability:	Finger/Stift/Handschuh / finger/pen/glov
CPU Typ:	Pentium
CPU Model:	N4200
CPU speed:	1,1 GHz
CPU cores:	4
RAM size (MB):	4096
RAM Typ:	DDR4
RAM speed:	2400
SSD design:	M.2
SSD capacity:	128
SSD number:	1
safety:	TPM 2.0 und Kensington Lock
WLAN:	Ja / yes
WLAN-Standard:	IEEE 802.11 a/b/g/n/ac
Bluetooth:	Ja / yes
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
Video:	1x Mirco HDMI
USB:	1x USB 3.0 (Type A), 1x USB 3.0 (Type C)
serial:	1x RS-232 über USB-C Adapter (optional)
LAN:	1x RJ45 über USB-C Adapter (optional)
Card Slot:	1x Micro SD Slot
Audio:	1x Audio Combo Conn.(Mic in/Line out)
Power:	1x 19 V/DC, DC plug
Docking connector:	1x 19-pin Docking Connector
controls:	4 Keys: Power, Volume, Fn1, Fn2
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	19 V/DC
voltage input AC:	100 - 240 V/AC
battery:	7.7V, 5900 mAh Li-Polymer Battery (2S1P)
battery Hot-Swap:	Ja / yes

Related links to "M116P"

- [Do you have any questions concerning this product?](#)
- [Further products by Winmate](#)

Available downloads:

- [Download Drawing Tablet-PC M116P 201008](#)
- [Download CE Konformitätserklärung DoC M116P-RED_20211004](#)