

Order number: 23221003
Open text field 2: 21,5 Zoll (16:9) Edelstahl-Panel-PC der ES-Serie, Intel Celeron N2930
Manufacturer: Winmate
Weight:10.7 kg

W22IB3S-65A3

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "W22IB3S-65A3"

Schutzart: rundum IP65 inkl. der Schnittstellen
Maße: (BxHxT) 550x340x64.8 mm, VESA-Montageschnittstelle (100x200 mm).
Integrierter 21.5" (16:9) TFT LCD Bildschirm, Helligkeit einstellbar max. 250 cd/m², Auflösung 1920 x 1080 Bildpunkte.
Rückseitige Kontrollelemente: Power, Reset.
All-In-One Mainboard mit Intel Celeron Bay Trail-M N2930 (Ultra-Low-Voltage), 2 x Mini-PCIe Slot (intern, 1 x SATA SSD/1 x W-LAN Modul USB 2.0), Grafik shared memory, Audio (Realtek ALC886),
Vorhandene Schnittstellen (inkl. Kabel mit IP65-geschützten Anschlüssen):
1 x RS-232, 2 x USB 2.0, 1 x LAN 10/100/1000 Mbps (Intel WG82574L),
1 x Power 12 V/DC inkl. externes Netzteil mit 100-240 V/AC.
Konfiguration:
- CPU: Intel Celeron Bay Trail-M N2930, 4x 1.83 GHz (Ultra-Low-Voltage)
- RAM: 8192 MB DDR3L-SODIMM
- SSD: 128 GB, mSATA
- TOUCH: resistiver PREMIER-Touchscreen, RS-232
Ursprungsland: Taiwan

article group specification:	2322
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	ES-Serie
Manufacturer item number:	W22IB3S-65A3
mechanics:	Chassis Edelstahl / stainless steel (VES
dimensions width:	55,0
dimensions height:	34,0
dimensions depth:	5,86
weight:	10,7
Material housing:	Edelstahl / stainless steel

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Material Front :	Edelstahl / stainless steel
protection front:	IP65
protection device:	IP65
colour:	Edelstahl gebürstet / brushed stainless
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 200 x 100 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
cooling:	lüfterlos / fanless
Display-diagonal (inch):	21,5
aspect ratio:	16:9
resolution:	1920 x 1080
brightness:	250 cd/m²
contrast:	3000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Resistive Touch
Touch Interface:	USB
Manufacturer controller:	Premier
voltage input DC:	12 V/DC (M12 type)
external power supply:	12 V/DC, 100 - 240 V/AC, 4-pin
USB:	2 x USB 2.0 (M12 type)
serial:	1 x RS-232 (M12 type)
LAN:	1x RJ45 - 10/100/1000 Mbps (M12 type)
CPU Typ:	Celeron
CPU Model:	N2930
CPU 64bit:	Ja
CPU speed:	1,83 GHz
CPU cores:	4
CPU socket:	FCBGA1170
RAM size (MB):	8192
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1600
Grafik Controller:	Intel HD Graphics Z3700 series
safety:	TPM 2.0
CPU class:	Atom / Celeron
SSD design:	mSATA
SSD max. number:	1
SSD capacity (GB):	128
Ethernet connections:	1 x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Ethernet Controller :	2x Intel I210-AT
operating temperatur min.:	0°C

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

operating temperatur max.:	45°C
warranty:	24 Monate / 24 months

Related links to "W22IB3S-65A3"

- Do you have any questions concerning this product?
- Further products by Winmate

Available downloads:

Download CE_Panel-PC ES-Serie Gebrauchsanleitung 20190130
Download CE Konformitätserklärung DoC Panel-PC WM 22W-IB32-ES-x_20190130
Download Drawing Panel-PC WM 22W-IB32-ES 201007

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de