

Order number: 25100057
Open text field 2: 10,1 Zoll (16:10) Rugged Industrie-Tablet-PC, Intel Pentium N4200, Windows 10 IoT Enterprise
Manufacturer: Winmate
Weight:1.2 kg

M101P - BARCODE/RFID

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "M101P - BARCODE/RFID"

Tablet PC for professional use Ruggedized Tablet in sturdy aluminium housing Protection class IP65 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810G) Multi-touch (PCAP) with Glove / Rain / Stylus modes Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc. Long-term availability

article group specification:	2510
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M101P
mechanics:	Rugged Tablet PC
dimensions width:	27,19
dimensions height:	19,73
dimensions depth:	1,95
weight:	1,2
Material housing:	Aluminium - Magnesium
protection device:	IP65
colour:	Schwarz / black
VESA-Mounting Interface:	Optional / optional
cooling:	lüfterlos / fanless
Display-diagonal (inch):	10,1
aspect ratio:	16:10
resolution:	1920 x 1200
brightness:	800 cd/m²
contrast:	800:1

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capactive / Multi-Touch
usability:	Finger/Stift/Handschuh / finger/pen/glov
CPU Typ:	Pentium
CPU Model:	N4200
CPU speed:	1,1 GHz
CPU cores:	4
RAM size (MB):	8192
RAM Typ:	SO-DDR4
RAM speed:	1600
SSD design:	M.2
SSD capacity:	256
SSD number:	1
safety:	TPM 2.0 und Kensington Lock
WLAN:	Ja / yes
WLAN-Standard:	IEEE 802.11 a/b/g/n/ac
Bluetooth:	Ja / yes
WWAN:	Ja / yes
WWAN-Standard:	4G/LTE/3G
Ethernet_connections:	Nein / no
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
Barcode:	1D/2D Barcode reader
RFID:	HF RFID reader
Video:	1x Mirco HDMI
USB:	1x USB 3.0 (Type A), 1x USB 3.0 (Type C)
Card Slot:	1x Micro SD Slot
Audio:	1x Audio Combo Conn.(Mic in/Line out)
Power:	1x 12-19 V/DC, DC plug
Docking connector:	1x 19-pin Docking Connector
controls:	6 Keys: Power, Home, 2x Volume, 2x Funct
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	12-19 V/DC
voltage input AC:	100 - 240 V/AC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

battery:	7.7V, 5900 mAh Li-Polymer Battery (2S1P)
battery Hot-Swap:	Ja / yes

Related links to "M101P - BARCODE/RFID"

- Do you have any questions concerning this product?
- Further products by Winmate

Available downloads:

Download CE Konformitätserklärung DoC M101P-RED_201008
Download Drawing Tablet-PC M101P 201008
Download Zubehör Accessories M101 Industrial Tablet PC - Charging
Download Zubehör Accessories M101 Industrial Tablet-PC - Data Capture
Download Zubehör Accessories M101 Industrial Tablet-PC - Docking Stations
Download Zubehör Accessories M101 Industrial Tablet-PC - Hand + Shoulder Strap
Download Zubehör Accessories M101 Industrial Tablet-PC - Mobile Printers
Download Zubehör Accessories M101 Industrial Tablet-PC

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de