



**Order number:** 51701210  
**Open text field 2:** 17,0 Zoll (4:3) LCD-Industriemonitor  
**Manufacturer:** Winmate  
**Weight:** 4.8 kg

## S17L500-OFM1\_PMA

### Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

### Product information "S17L500-OFM1\_PMA"

Industrial LCD for professional use Industrial monitor in sturdy sheet steel design Robust aluminum front panel (IP65-protected) Designed for industrial applications in continuous operation Panelmount installation with rear screwed bolts Long-term availability. 17" (4:3) active matrix TFT built-in LCD with aluminum front frame panel mount, "Type PMA", color RAL7035, with fixing bolts and rear sealing lip. Protection class: front IP65 Version: covered at the rear to prevent accidental contact (cage chassis) LCD dimensions: 410 x 330 x 58 mm, front panel dimensions: 483 x 399 x 5 mm, Resolution: 1280 x 1024 pixels Video input: 15 pin HD sub socket (VGA) + DVI + HDMI Supply voltage: 12 V/DC, incl. external power supply unit with 100-240 V/AC Temperature range: 0-50° C (operation), -10-60° C (storage) incl. resistive PREMIER touchscreen, USB Origin: Taiwan

article group specification:	517
Manufacturer:	WM
Manufacturer:	Wimate
series name:	WM-Serie
Manufacturer item number:	S17L500-OFM1
mechanics:	Panel Mount
dimensions width:	48,3
dimensions height:	39,9
dimensions depth:	6,3
weight:	4,8
Material housing:	Metallgehäuse / Metal housing
Material Front :	Aluminium / aluminum
protection front:	IP65
protection device:	IP20
colour:	RAL 7035 / light grey
controls:	5 Keys: -, +, Power, Esc, Enter
VESA-Mounting Interface:	VESA 75 x 75 mm
mounting:	Einbau von vorne / front installation
Display-diagonal (inch):	17,0
aspect ratio:	4:3

resolution:	1280 x 1024
brightness:	350 cd/m <sup>2</sup>
contrast:	1000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Resistive Touch
Touch Interface:	USB
Manufacturer controller:	Premier
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, DC plug
VGA:	1 x 15-pin D-sub
DVI:	1 x DVI-D
HDMI:	1 x HDMI
operating temperatur min.:	0°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

## Related links to "S17L500-OFM1\_PMA"

- [- Do you have any questions concerning this product?](#)
- [- Further products by Winmate](#)

## Available downloads:

- [Download CE Konformitätserklärung DoC LCD WM 17-Vu-x-y-z\\_20190130](#)
- [Download Drawing Industrie-LCD WM 17-...-PMA+PME \(Panelmount\)\\_20200804](#)
- [Download Drawing WM 17-...-PMA+PME \(Panelmount\) Installation 190228](#)