


Order number: 23100491

Open text field 1: -1

Open text field 2: 10,1 Zoll (16:10) Rugged Industrie-Tablet-

Manufacturer: Winmate

Weight: 1 kg

M101M8

Price on request

 Prices plus VAT [plus shipping costs](#)

 Ready to ship today,
 Delivery time appr. 1-3 workdays

Product information "M101M8"

Tablet PC for professional use Ruggedized Tablet in sturdy aluminium housing Protection class IP65 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810G) Multi-touch (PCAP) with Glove / Rain / Stylus modes Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc.

article group specification:	2310
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M101M8
mechanics:	Rugged Tablet PC
dimensions width:	27,18
dimensions height:	19,72
dimensions depth:	1,9
weight:	1,0
Material housing:	Aluminium - Magnesium
protection device:	IP65
colour:	Schwarz / black
cooling:	l�fterlos / fanless
Display-diagonal (inch):	10,1
aspect ratio:	16:10
resolution:	1280 x 800
brightness:	300 cd/m ²
contrast:	1000:1

Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch
usability:	Finger/Stift/Handschuh / finger/pen/glov
CPU Typ:	ARM Cortex
CPU Model:	A53
CPU speed:	1,3 GHz
CPU cores:	8
RAM size (MB):	2048
RAM Typ:	LPDDR3
SSD design:	mSATA
SSD capacity:	16
SSD number:	1
SSD number max.:	1
safety:	Kensington lock
WLAN:	Ja / yes
WLAN-Standard:	IEEE 802.11 a/b/g/n
Bluetooth:	Ja / yes
WWAN:	Ja / yes
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
Barcode:	2D Barcode-Reader
Video:	1x Mirco HDMI
USB:	1x USB 2.0
Card Slot:	1x Micro SD Slot
Audio:	1x Audio Combo Conn.(Mic in/Line out)
Docking connector:	1x 19-pin Docking Connector
controls:	5 Keys: 1x Power, 2x Volume, 2x Function
operating system:	Android 5.1
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, DC plug
battery:	7.4V, 5140 mAh (typ.) Li-Polymer Battery
battery Hot-Swap:	Ja / yes

Related links to "M101M8"

[- Do you have any questions concerning this product?](#)

[- Further products by Winmate](#)

Available downloads:

[Download CE Konformitätserklärung DoC Tablet-PC M101M8_20190130](#)

[Download Drawing Tablet-PC M101M8 190228](#)