



Order number: 23100493

Open text field 1: -1

Open text field 2: B-Ware, 10,1 Zoll (16:9) Vehicle Mount Computer VM

Manufacturer: Winmate

Weight: 1.7 kg

FM10

Price on request

Prices plus VAT [plus shipping costs](#)

Ready to ship today,
Delivery time appr. 1-3 workdays

Product information "FM10"

Tablet PC ready for vehicle and forklift installation Ruggedized Tablet and docking unit in sturdy magnesium alloy housing Protection class IP65 all around incl. Interfaces Shock and vibration protected (MIL-STD-810G) Antiscratch resistive touch (finger & stylus) SMA connector for external antenna 10-60 V input, wide operating temperature range, mounting accessories etc. Field-replaceable front unit (Tablet) reduces service costs and downtime The ideal partner for warehouse, logistics, automotive, outdoor etc.

article group specification:	2310
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
series name:	Vehicle Mounted Computer
Manufacturer item number:	FM10
mechanics:	Vehicle Mount Computer
dimensions width:	26,8
dimensions height:	21,4
dimensions depth:	3,5
weight:	1,7
Material housing:	Magnesium Legierung / Magnesium alloy
protection device:	IP65
colour:	Schwarz / black
cooling:	l�fterlos / fanless
Display-diagonal (inch):	10,1
aspect ratio:	16:9
resolution:	1024 x 768
brightness:	400 cd/m ²
contrast:	1200:1

Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch
usability:	Finger/Stift / finger/pen
CPU Typ:	Atom
CPU Model:	E3845
CPU speed:	1,91 GHz
CPU cores:	4
RAM size (MB):	4096
RAM Typ:	SO-DDR3L
RAM speed:	1600
SSD design:	M.2
SSD capacity:	64
SSD number:	1
WLAN:	Ja / yes
WLAN-Standard:	IEEE 802.11 a/b/g/n/ac
Bluetooth:	Ja / yes
Camera front:	Ja / yes
Camera front resolution:	2MP
USB:	1x USB 3.0
Card Slot:	1x SIM Slot, 1x SD Slot
Docking connector:	1x 19-pin Docking Connector
operating system:	Windows 10
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	10 V-60 V
battery:	7.6V, 5800 mAh Li-Polymer Battery (2S1P)

Related links to "FM10"

- [- Do you have any questions concerning this product?](#)
- [- Further products by Winmate](#)

Available downloads:

- [Download CE Konformitätserklärung DoC VMC FM10_20190130](#)
- [Download Drawing Vehicle Mounted Computer FM10 190228](#)