

Order number: 23152502
Open text field 2: 15,0 Zoll (4:3) Panel-PC, Intel Pentium N4200
Manufacturer: TL Electronic, Bergkirchen-Feldgeding

R15IP3S-GCC3

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "R15IP3S-GCC3"

Built-in Panel PC for professional use Industrial Panel PC in sturdy steel sheet design Robust plastic front panel (IP65 protected) Shock and vibration resistant acc. MIL-STD-810F/G Designed for industrial applications in continuous operation Panelmount installation with rear screwed bolts Long-term availability

article group specification:	2315
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	GC-Serie
Manufacturer item number:	R15IP3S-GCC3
mechanics:	Chassis (VESA-Mounting)
dimensions width:	36,34
dimensions height:	27,78
dimensions depth:	4,45
Material housing:	Stahlblech / steel sheet
Material Front :	Kunststoff / plastic
protection front:	IP65
colour:	schwarz / black
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 100 x 100 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
cooling:	lüfterlos / fanless
Display-diagonal (inch):	15,0
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	300 cd/m²

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

contrast:	2000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Projected Capactive / Multi-Touch
Touch Interface:	USB
Manufacturer controller:	P-CAP Touchcontroller
voltage input DC:	12 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, 4-pin
USB:	2 x USB 3.0
serial:	1 x RS-232/422/485
Audio:	2 x Speaker
LAN:	2x RJ45 - 10/100/1000 Mbps
CPU Typ:	Pentium
CPU Model:	N4200
CPU 64bit:	Ja
CPU speed:	1,1 GHz
CPU cores:	4
CPU socket:	FCBGA1296
RAM size (MB):	4096
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1600
Grafik Controller:	Intel HD Graphics 505
safety:	TPM 2.0
CPU class:	Pentium
SSD design:	M.2
SSD max. number:	1
SSD capacity (GB):	64
Ethernet connections:	2 x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Ethernet Controller :	2 x Intel 2.5Gbps Ethernet Controller
WLAN :	Optional / optional
Bluetooth :	optional / optional
Betriebssystem:	Optional
operating-system language version:	deutsch / english / italian
operating temperatur min.:	0°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Related links to "R15IP3S-GCC3"

- Do you have any questions concerning this product?
- Further products by TL Electronic, Bergkirchen-Feldgeding

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Available downloads:

Download Drawing Panel-PC R15IP3S-GCC3_12092022
Download CE Konformitätserklärung DoC R15IP3S-GCC3

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de