



Order number: 25140003

Open text field 2: 14,0 Zoll Rugged Industrie-Tablet-PC, Intel Core i5-1135G7, Windows 10 IoT Enterprise

Manufacturer: Winmate

Weight: 1.7 kg

M140TG

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "M140TG"

Rugged Tablet-PC for professional use Shock, vibration and drop protected (MIL-STD-810H) Multi-touch (PCAP) Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc. Long-term availability

article group specification:	2514
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M140TG
mechanics:	Rugged Tablet PC
dimensions width:	34,19
dimensions height:	22,47
dimensions depth:	2,54
weight:	1,7
Material housing:	Aluminium - Magnesium
protection device:	IP65
colour:	Schwarz / black
cooling:	aktiv / fan cooling
Display-diagonal (inch):	14,0
resolution:	1920 x 1080
brightness:	700 cd/m²
contrast:	800:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capacitive / Multi-Touch
usability:	Finger/Stift/Handschuh / finger/pen/glov

CPU Typ:	Core i5
CPU Model:	1135G7
CPU speed:	2,40 GHz
CPU cores:	4
RAM size (MB):	4096
RAM max. Größe (MB):	32768
RAM Typ:	SDRAM-DDR4
SSD capacity:	128
SSD number:	1
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
RFID:	Optional / optional
Video:	1x Mirco HDMI (optional)
USB:	2x USB 3.0 (Type A), 1x USB 3.0 (Type C)
LAN:	1x RJ45 - 10/100 Mbps
Card Slot:	1x Micro SDXC Slot, 1x Micro SIM Slot
Audio:	1x Audio Combo Conn.(Mic in/Line out)
Power:	1x 19 V/DC, DC plug
Docking connector:	1x 19-pin Docking Connector
controls:	4 Keys: 1x Power, 3x Function
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810H Method 516.8 Procedure I
Vibration:	MIL-STD-810H Method 514.8 Procedure I
Drop:	MIL-STD-810H Method 516.8, 3 ft
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	10.8V 2400 mAh Li-Polymer Battery (3S1P)
battery Hot-Swap:	Optional / optional

Related links to "M140TG"

- [- Do you have any questions concerning this product?](#)
- [- Further products by Winmate](#)

Available downloads:

[Download Drawing Tablet-PC M140TG 221209](#)

[Download CE Konformitätserklärung DoC Tablet-PC M140TG](#)