

Order number: 25050008
Open text field 2: 5,0 Zoll Industrie-PDA, Cortex A73 + A53, Android 11
Manufacturer: Winmate
Weight:0.315 kg

E500RM9

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "E500RM9"

Rugged Industrial PDA for professional use Ruggedized handheld in sturdy housing with all-around elastomeric rubber Protection class IP65 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810H) 10-point multi-touch with hand / glove / rain mode, sunlight readable (optical bonding) Battery life up to 20 h The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc. Long-term availability

article group specification:	2505
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	Rugged Industrial PDA
Manufacturer item number:	E500RM9
mechanics:	Handheld
dimensions width:	85,9
dimensions height:	16,32
dimensions depth:	2,25
weight:	0,315
Material housing:	Kunststoff / plastic
protection device:	IP65
colour:	Schwarz / black
cooling:	lüfterlos / fanless
Display-diagonal (inch):	5,0
aspect ratio:	16:9
resolution:	1280 x 720
brightness:	500 cd/m²
contrast:	800:1
Display-Technology:	LCD, LED Backlight

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Touch-Screen :	Projected Capactive / Multi-Touch
usability:	Finger/ Handschuh/ finger/ glove
CPU Typ:	ARM Cortex
CPU Model:	A73 + A53
CPU speed:	2,0 GHz
CPU cores:	8
RAM size (MB):	4096
SSD capacity:	64
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Camera front:	Ja / yes
Camera front resolution:	8MP
Camera rear:	Ja / yes
Camera rear resolution:	13MP
Barcode:	Optional / optional
RFID:	Optional / optional
Finger Print:	Optional / optional
USB:	1x Micro USB OTG
Docking connector:	1x 19-pin Docking Connector
controls:	8 Keys: Power, 7x Function
operating system:	Android 11
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810H Method 516.6 Procedure I
Vibration:	MIL-STD-810H Method 514.8 Procedure I
Drop:	MIL-STD-810H Method 516.6, 4 ft
voltage input DC:	5 V/DC
external power supply:	5 V/DC, 100 - 240 V/AC, DC plug
battery:	3.7V, 3900 mAh Li-ion Battery
battery Hot-Swap:	Optional / optional

Related links to "E500RM9"

- Do you have any questions concerning this product?
- Further products by Winmate

Available downloads:

Download Drawing PDA E500RM9 230414

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de