

Order number: 25100076
Open text field 2: 10,1 Zoll (16:10) Healthcare Rugged Tablet-PC, Intel Pentium N4200, Windows 10 IoT Enterprise
Manufacturer: Winmate
Weight:1.2 kg

M101P

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "M101P"

10.1” (1920 x 1200) IPS LED Panel with direct optical bonding Intel® Pentium® N4200 Windows Healthcare Rugged Tablet Protection class IP65 all around incl. Interfaces Ruggedized tablet in aluminum case equipped with antimicrobial properties Choice of various standard and opional accessories configurable Shock, vibration and drop protected (MIL-STD-810G) Multi-touch (PCAP) with Glove / Rain / Stylus modes

article group specification:	2510
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M101P-ME
mechanics:	Rugged Tablet PC
dimensions width:	27,19
dimensions height:	19,73
dimensions depth:	1,95
weight:	1,2
Material housing:	Aluminium - Magnesium
protection device:	IP65
colour:	weiß / white
cooling:	lüfterlos / fanless
Display-diagonal (inch):	10,1
aspect ratio:	16:9
resolution:	1920 x 1200
brightness:	650 cd/m²
contrast:	800:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capactive / Multi-Touch

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

CPU Typ:	Pentium
CPU Model:	N4200
CPU speed:	1,1 GHz
CPU cores:	4
RAM size (MB):	4096
RAM max. Größe (MB:	8192
SSD capacity:	128
SSD number:	1
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
Video:	1x HDMI (optional)
USB:	1x USB 3.0 (Type A), 1x USB 3.0 (Type C)
Card Slot:	1x Micro SDXC Slot, 1x Micro SIM Slot
Docking connector:	1x 19-pin Docking Connector
controls:	6 Keys: Power, 5x Function
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	0°C
operating temperatur max.:	35°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	7.4V, 5140 mAh (typ.) Li-Polymer Battery
battery Hot-Swap:	Ja / yes

Related links to "M101P"

- Do you have any questions concerning this product?
- Further products by Winmate

Available downloads:

Download Drawing Tablet-PC M101P-ME 261007.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de