

Order number: 23152541
Open text field 2: 15,0 Zoll (4:3) Panel-PC der ATEX-Serie, Intel Atom N2600
Manufacturer: TL Electronic, Bergkirchen-Feldgeding

R15ID3S-65EX

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "R15ID3S-65EX"

13.3" (1920 x 1080) Resolution Transflective TFT-LCD Panel Intel® Core™ i5-7200U Defence Ultra Rugged Tablet EX Certificate: Class1, Division 2 & ATEX Zone 2 device certified for hazardous area application Fanless, streamlined enclosure for highly efficient heat dissipation Protection class IP65 all around incl. connectors Shock, vibration and drop protected (MIL-STD-810G) 5 wire Resistive Touch Screen (Explosion-proof) VESA Mount

article group specification:	2315
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
Manufacturer item number:	R15ID3S-65EX
dimensions width:	39,6
dimensions height:	31,0
dimensions depth:	4,9
Material housing:	Edelstahl / stainless steel
Material Front :	Edelstahl / stainless steel
protection device:	IP65
colour:	Aluminium eloxiert / anodized aluminum
controls:	2 Keys: Power, Reset
VESA-Mounting Interface:	VESA 100 x 100 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
cooling:	lüfterlos / fanless
Display-diagonal (inch):	15,0
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	550 cd/m²
contrast:	2000:1

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	5 Wire Resistive
Touch Interface:	USB
Manufacturer controller:	Premier
voltage input DC:	9-36 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, 4-pin
USB:	2 x USB 2.0 (M12 type)
serial:	1 x RS-232 (M12 type)
LAN:	1x RJ45 - 10/100/1000 Mbps (M12 type)
CPU Typ:	Atom
CPU Model:	N2600
CPU 64bit:	Ja
CPU speed:	1,6GHz
CPU cores:	2
CPU socket:	FCBGA559
RAM size (MB):	4096
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1600
CPU class:	Atom / Celeron
SSD design:	mSATA
SSD max. number:	1
SSD capacity (GB):	128
Ethernet connections:	1 x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Betriebssystem:	Optional
operating temperatur min.:	-20°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Related links to "R15ID3S-65EX"

- Do you have any questions concerning this product?
- Further products by TL Electronic, Bergkirchen-Feldgeding

Available downloads:

Download Drawing Panel-PC R15ID3S-65EX 12062023.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de