



Order number: 23191858
Open text field 2: 19,0 Zoll (4:3) Multitouch-Panel-PC, Intel Atom N2600
Manufacturer: Winmate
Weight: 9.5 kg
Height: 38.5 cm
Width: 6.3 cm
Length: 46 cm

R19L300-MRA2ID3S

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "R19L300-MRA2ID3S"

19" (1280 x 1024) Marine Panel PC Intel Atom® N2600 dual-core processor Meet the requirements of Industrial marine standards, including IEC60945 4th Edition, DNVGL-CG-0339, IACS E10 Protection class IP66 Front side protected, IP 54 Back side protected Dimming knob control backlight brightness from nearly 0% to 100% Resistive Touchscreen / Anti-Reflection Protection Glass (Optional) 24V DC-in with Isolation (Approval by Certificate) 9 to 36V DC Input Acceptable VESA Mount/ Panel Mount

article group specification:	2319
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
Manufacturer item number:	R19L300-MRA2ID3S
mechanics:	Panel Mount
dimensions width:	38,45
dimensions height:	44,4
dimensions depth:	7,5
weight:	9,5
Material housing:	Stahlblech / steel sheet
Material Front :	Aluminium / aluminum
protection front:	IP66
colour:	schwarz / black
controls:	3 Keys: Power On/Of, Reset, Brightness
VESA-Mounting Interface:	VESA 100 x 100 mm
mounting:	Einbau von vorne / front installation
cooling:	lüfterlos / fanless
Display-diagonal (inch):	19,0
aspect ratio:	4:3
resolution:	1280 x 1024

brightness:	350 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Resistive Touch
Touch Interface:	USB
Manufacturer controller:	Premier
voltage input DC:	24 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, 4-pin
VGA:	1 x 15-pin D-sub
USB:	2 x USB 2.0
serial:	1 x RS232/422/485, 4 x RS232
LAN:	2x RJ45 - 10/100/1000 Mbps
chipset:	Intel NM10
CPU Typ:	Atom
CPU Model:	N2600
CPU 64bit:	Ja
CPU speed:	1,6GHz
CPU cores:	2
CPU socket:	FCBGA559
RAM size (MB):	4096
RAM Number of benches:	1
RAM Typ:	SO-DDR3L
RAM speed:	1600
SSD design:	mSATA
SSD max. number:	1
SSD capacity (GB):	128
Ethernet connections:	2 x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Betriebssystem:	Optional
operating temperatur min.:	-15°C
operating temperatur max.:	55°C
warranty:	24 Monate / 24 months

Related links to "R19L300-MRA2ID3S"

- [- Do you have any questions concerning this product?](#)
- [- Further products by Winmate](#)

Available downloads:

[Download Drawing Panel-PC R19L300-MRA2ID3S 13062023.pdf](#)