

**Order number:** 51901601
**Open text field 2:** 19,0 Zoll (4:3) Marine Display
**Manufacturer:** TL Electronic, Bergkirchen-Feldgeding

# R19L300-MRA1

## Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

### Product information "R19L300-MRA1"

19" (1280 x 1024) Marine Display Protection class IP66 Front side protected, IP 54 Back side protected Dimming knob control backlight brightness from nearly 0% to 100% User-friendly OSD control on the front marine display Enhanced shock and vibration resistance Resistive Touchscreen / Anti-Reflection Protection Glass (Optional) 24V DC-in with Isolation (Approval by Certificate) 9 to 36V DC Input Acceptable VESA Mount/ Panel Mount

| | |
|---|---|
| **article group specification:** | 519 |
| **Manufacturer:** | WM |
| **MatchcodeHersteller:** | nein |
| **Manufacturer:** | Winmate |
| **Manufacturer item number:** | R19L300-MRA1 |
| **mechanics:** | Panel Mount |
| **dimensions width:** | 48,3 |
| **dimensions height:** | 44,4 |
| **dimensions depth:** | 7,5 |
| **Material housing:** | Stahlblech / steel sheet |
| **Material Front :** | Aluminium / aluminum |
| **protection front:** | IP66 |
| **colour:** | schwarz / black |
| **controls:** | 8 Keys: Power, 7x Function |
| **VESA-Mounting Interface:** | VESA 100 x 100 mm |
| **mounting:** | Einbau von vorne / front installation |
| **Display-diagonal (inch):** | 19,0 |
| **aspect ratio:** | 4:3 |
| **resolution:** | 1280 x 1024 |
| **brightness:** | 400 cd/m² |
| **contrast:** | 1000:1 |

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

| | |
|---|---|
| **Display-Technology:** | LCD, LED Backlight |
| **Touch-Screen or glass:** | Resistive Touch |
| **Touch Interface:** | USB |
| **Manufacturer controller:** | Premier |
| **voltage input DC:** | 9-36 V/DC |
| **external power supply:** | 12 V/DC, 100 - 240 V/AC, 4-pin |
| **VGA:** | 1 x 15-pin D-sub |
| **DVI:** | 1 x DVI-D |
| **Video:** | 1 x Composite, 1 x S-Video |
| **serial:** | 2 x RS232 |
| **operating temperatur min.:** | -15°C |
| **operating temperatur max.:** | 55°C |
| **warranty:** | 24 Monate / 24 months |

## Related links to "R19L300-MRA1"

- Do you have any questions concerning this product?
- Further products by TL Electronic, Bergkirchen-Feldgeding

## Available downloads:

Download Drawing LCD R19L300-MRA1 13062023.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de