



Order number: 25100072

Open text field 2: 10,4 Zoll (4:3) Ultra Rugged Tablet PC, Intel Pentium N4200, Windows 10 IoT Enterprise

Manufacturer: Winmate

Weight: 2.4 kg

R10IP8M-RTT2ML

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "R10IP8M-RTT2ML"

10.4" (1024 x 768) Resolution Transflective TFT-LCD Panel Intel® Pentium® N4200 Defence Ultra Rugged Tablet Ruggedized tablet in sturdy Magnesium Alloy housing with all-around elastomeric rubber MIL-STD-38999 connector for LAN/USB2.0, RS232/RS422 and DC Power Input Adjustable Kickstand that is Convertible to a handle Protection class IP54 all around incl. connectors Shock, vibration and drop protected (MIL-STD-810G)

article group specification:	2510
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winnate
series name:	Ultra Rugged Tablet PC
Manufacturer item number:	R10IP8M-RTT2ML
mechanics:	Ultra Rugged Tablet PC
dimensions width:	26,6
dimensions height:	22,2
dimensions depth:	5,0
weight:	2,4
Material housing:	Magnesium Legierung / Magnesium alloy
protection device:	IP54
colour:	Schwarz / black, Grau / gray
cooling:	lüfterlos / fanless
Display-diagonal (inch):	10,4
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	1000 cd/m²
contrast:	700:1
Display-Technology:	LCD, LED Backlight

Touch-Screen :	Projected Capacitive / Multi-Touch
CPU Typ:	Pentium
CPU Model:	N4200
CPU speed:	1,1 GHz
CPU cores:	4
RAM size (MB):	4096
RAM max. Größe (MB):	8192
RAM Typ:	SO-DDR3L
RAM speed:	1866
SSD design:	M.2
SSD capacity:	64
SSD number:	1
safety:	TPM 2.0
WLAN:	Ja / yes
WLAN-Standard:	IEEE 802.11 a/b/g/n/ac
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Optional / optional
Camera rear:	Optional / optional
USB:	2x USB 3.0, 1x USB 2.0
serial:	1x RS-232/422
LAN:	1x RJ45 - 10/100 Mbps
Card Slot:	1x SIM Slot
Audio:	2 x 1 watt speaker
Power:	1x 9-36 V/DC, DC plug
controls:	7 Keys: Power, 6x Function
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
voltage input DC:	9-36 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	11.1V, 5200 mAh Li-ion Battery

Related links to "R10IP8M-RTT2ML"

- [- Do you have any questions concerning this product?](#)
- [- Further products by Winmate](#)

Available downloads:

[Download Drawing Tablet-PC R10IP8M-RTT2ML 230223](#)