



Order number: 51501548
Open text field 2: 15,0 Zoll (4:3) ATEX Display
Manufacturer: Winmate
Weight: 6.5 kg
Height: 31.1 cm
Width: 6.1 cm
Length: 38.4 cm

R15L600-65EX

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "R15L600-65EX"

15" 1024 x 768, 550 nits (Optional 1000 nits) LCD Panel Ex Certificate: Class 1, Division 2 & ATEX Zone 2 application certification rugged touchscreen Protection class IP65 all around incl. connectors Shock, vibration and drop protected (MIL-STD-810G) Resistive Touch Screen Bonding With Panel VESA Mount

article group specification:	515
Manufacturer:	WM
MatchcodeHersteller:	nein
Manufacturer:	Winnate
series name:	WM-Serie
Manufacturer item number:	R15L600-65EX
mechanics:	Chassis Edelstahl / stainless steel (VES
dimensions width:	39,6
dimensions height:	31,0
dimensions depth:	4,9
Material housing:	Edelstahl / stainless steel
Material Front :	Edelstahl / stainless steel
protection front:	IP65
protection device:	IP65
colour:	Edelstahl gebürstet / brushed stainless
controls:	5 Keys: -, +, Power, Esc, Enter
VESA-Mounting Interface:	VESA 100 x 100 mm
mounting:	Tragarm-, Standfuß-, Wandmontage / Suppo
Display-diagonal (inch):	15,0
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	550 cd/m²

contrast:	2000:1
Display-Technology:	LCD, LED Backlight
Touch-Screen or glass:	Resistive Touch
Touch Interface:	USB
Manufacturer controller:	Premier
voltage input DC:	9-36 V/DC
external power supply:	12 V/DC, 100 - 240 V/AC, 4-pin
VGA:	1 x 12-pin (M12 type)
USB:	1 x USB 2.0 (M12 type)
serial:	1 x RS-232 (M12 type)
operating temperatur min.:	-20°C
operating temperatur max.:	50°C
warranty:	24 Monate / 24 months

Related links to "R15L600-65EX"

- [- Do you have any questions concerning this product?](#)
- [- Further products by Winmate](#)

Available downloads:

[Download Drawing LCD R15L600-65EX 12062023.pdf](#)