



Order number: 25100073

Open text field 2: 10,4 Zoll (4:3) Ultra Rugged Tablet PC, Intel Core i5-8265U

Manufacturer: Winmate

Weight: 2.4 kg

R10IWK8M-RTT2GP

Price on request

Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "R10IWK8M-RTT2GP"

10.4" (1024 x 768) Resolution Transflective TFT-LCD Panel Intel® Core® i5 1135G7 Defence Ultra Rugged Tablet Ruggedized tablet in sturdy Magnesium Alloy housing with all-around elastomeric rubber MIL-STD-38999 connector for LAN/USB2.0, RS232/RS422 and DC Power Input Adjustable Kickstand that is Convertible to a handle Protection class IP54 all around incl. connectors Shock, vibration and drop protected (MIL-STD-810G)

article group specification:	2510
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Wimate
series name:	Ultra Rugged Tablet PC
Manufacturer item number:	R10IWK8M-RTT2GP
mechanics:	Ultra Rugged Tablet PC
dimensions width:	26,6
dimensions height:	22,4
dimensions depth:	5,04
weight:	2,4
Material housing:	Magnesium Legierung / Magnesium alloy
protection device:	IP54
colour:	Schwarz / black
cooling:	lüfterlos / fanless
Display-diagonal (inch):	10,4
aspect ratio:	4:3
resolution:	1024 x 768
brightness:	700 cd/m ²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight

Touch-Screen :	Resistive Touch
CPU Typ:	Core i5
CPU Model:	8265U
CPU speed:	1,6 GHz
CPU cores:	4
RAM size (MB):	4096
RAM max. Größe (MB):	32768
RAM Typ:	SO-DDR4
RAM speed:	2400
SSD design:	M.2
SSD capacity:	128
SSD number:	1
safety:	TPM 2.0
WLAN:	Ja / yes
Bluetooth:	Ja / yes
WWAN:	Optional / optional
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Optional / optional
Camera rear:	Optional / optional
Barcode:	Optional / optional
USB:	2x USB 3.2
serial:	1x RS-232
LAN:	1x RJ45 - 10/100 Mbps
Card Slot:	1x Micro SD Slot, 1x Micro SIM Slot
Audio:	1x Mic in/Line out, 2x Speaker
operating temperatur min.:	-10°C
operating temperatur max.:	50°C
Shock:	MIL-STD-810G Method 516.6 Procedure I
Vibration:	MIL-STD-810G Method 514.6 Procedure I
Drop:	MIL-STD-810G Method 516.6, 4 ft
external power supply:	19 V/DC, 110 - 240 V/AC, DC plug
battery:	11.1V, 5200 mAh Li-ion Battery

Related links to "R10IWK8M-RTT2GP"

- [- Do you have any questions concerning this product?](#)
- [- Further products by Winmate](#)

Available downloads:

[Download Drawing Tablet-PC R10IWK8M-RTT2GP 230224](#)