

Order number: 25110022
Open text field 1: -1
Open text field 2: 11,6 Zoll (16:9) Rugged Industrie-Tablet-PC, Intel Core i5-1135G7, Windows 10 IoT
Manufacturer: Winmate
Weight:1.5 kg

M116TG

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "M116TG"

Tablet PC for professional use Ruggedized Tablet in sturdy aluminium housing Protection class IP65 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810H) Multi-touch (PCAP) with Glove / Rain / Stylus modes Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc. Long-term availability

article group specification:	2511
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	Rugged Industrial Tablet PC
Manufacturer item number:	M116TG
mechanics:	Rugged Tablet PC
dimensions width:	30,1
dimensions height:	20,2
dimensions depth:	2,25
weight:	1,5
Material housing:	Aluminium - Magnesium
protection device:	IP65
colour:	Schwarz / black
cooling:	aktiv / fan cooling
Display-diagonal (inch):	11,6
aspect ratio:	16:9
resolution:	1920 x 1080
brightness:	850 cd/m²
contrast:	1000:1
Display-Technology:	LCD, LED Backlight

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Touch-Screen :	Projected Capactive / Multi-Touch
usability:	Finger/Stift/Handschuh / finger/pen/glov
CPU Typ:	Core i5
CPU Model:	1135G7
CPU speed:	2,40 GHz
CPU cores:	4
RAM size (MB):	8192
RAM Typ:	SDRAM-DDR4
SSD design:	M.2
SSD capacity:	256
SSD number:	1
safety:	TPM 2.0 und Kensington Lock
WLAN:	Ja / yes
Bluetooth:	Ja / yes
Ethernet_connections:	1x RJ-45
Ethernet data transfer:	1 x Gigabit-LAN
Camera front:	Ja / yes
Camera front resolution:	2MP
Camera rear:	Ja / yes
Camera rear resolution:	8MP
USB:	1x USB 3.0 (Type A), 1x USB 3.0 (Type C)
LAN:	1x RJ45 - 10/100/1000 Mbps
Card Slot:	1x Micro SDXC Slot, 1x Micro SIM Slot
Audio:	1x Audio Combo jack 3.5mm
Power:	1x 19 V/DC, DC plug
Docking connector:	1x 19-pin Docking Connector
controls:	7 Keys: Power, 6x Function
operating system:	Windows 10 IoT Enterprise
operating temperatur min.:	-20°C
operating temperatur max.:	60°C
Shock:	MIL-STD-810H Method 516.8 Procedure I
Vibration:	MIL-STD-810H Method 514.8 Procedure I
Drop:	MIL-STD-810H Method 516.8, 4 ft
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	10.8V, 4700 mAh Li-Polymer Battery (3S2P

Related links to "M116TG"

- Do you have any questions concerning this product?
- Further products by Winmate

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Available downloads:

Download Drawing Tablet-PC M116TG 221208.pdf
Download CE Konformitätserklärung DoC Tablet-PC M116TG.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de