

Order number: 25150001
Open text field 2: 15,6 Zoll Rugged Industrial Laptop, i7-12700H, Windows 10 IoT Enterprise
Manufacturer: Winmate
Weight:2.8 kg

L156AD-M1

Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

Product information "L156AD-M1"

Rugged Laptop for professional use Shock, vibration and drop protected (MIL-STD-810H) Multi-touch (PCAP) Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc. Long-term availability

article group specification:	2515
Manufacturer:	WM
Matchcode manufacturer:	nein
Manufacturer:	Winmate
series name:	Rugged Laptop
Manufacturer item number:	L156AD-M1
mechanics:	Rugged Laptop
dimensions width:	38,76
dimensions height:	3,88
dimensions depth:	25,6
weight:	2,8
protection device:	IP65
colour:	Schwarz / black
cooling:	aktiv / fan cooling
Display-diagonal (inch):	15,6
resolution:	1920 x 1080
brightness:	800 cd/m²
contrast:	800:1
Display-Technology:	LCD, LED Backlight
Touch-Screen :	Projected Capactive / Multi-Touch
CPU Typ:	Core i7
CPU Model:	12700H

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

CPU speed:	2,30 GHz
CPU cores:	14
RAM size (MB):	32768
RAM max. Größe (MB:	65536
RAM Typ:	SDRAM-DDR5
SSD design:	M.2
SSD capacity:	256
SSD number:	1
safety:	TPM 2.0
WLAN:	Ja / yes
Bluetooth:	Ja / yes
Ethernet_connections:	2x RJ-45
Ethernet data transfer:	2 x Gigabit-LAN
Camera front:	Ja / yes
Camera front resolution:	2MP
RFID:	Optional / optional
Finger Print:	Optional / optional
Video:	1x HDMI 4K (optional)
USB:	3x USB 3.0 (Type A), 1x USB 3.0 (Type C)
serial:	1x RS-232 (DB9)
LAN:	2x RJ45 - 10/100/1000 Mbps
Card Slot:	1x Micro SDXC Slot
Audio:	1x Audio Combo jack 3.5mm
Power:	1x 19 V/DC, DC plug
controls:	5 Keys: Power, 4x Function Key
operating system:	Windows 11 IoT Enterprise LTSC
operating system optional:	Windows 10 IoT Enterprise LTSC
operating temperatur min.:	-20°C
operating temperatur max.:	60°C
Shock:	MIL-STD-810H Method 516.8 Procedure I
Vibration:	MIL-STD-810H Method 514.8 Procedure I
Drop:	MIL-STD-810H Method 516.8, 3 ft
voltage input DC:	19 V/DC
external power supply:	19 V/DC, 100 - 240 V/AC, DC plug
battery:	2x 11.55V, 3220mAh Li-Ion Battery (3S1P)
battery Hot-Swap:	Ja / yes

Related links to "L156AD-M1"

- Do you have any questions concerning this product?
- Further products by Winmate

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

Available downloads:

Download Drawing L156AD-M1 Rugged Laptop.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de