

**Order number:** 25100099
**Open text field 2:** 10,1 inch (16:10) Rugged Industrial-Tablet-PC, Intel Core i5-1235U, Windows 10 IoT
**Manufacturer:** Winmate
**Weight:**1.2 kg

# M101AD

## Price on request

Prices plus VAT plus shipping costs

Delivery time: upon request

### Product information "M101AD"

Tablet PC for professional use Ruggedized Tablet in sturdy aluminium housing Protection class IP65 all around incl. Interfaces Shock, vibration and drop protected (MIL-STD-810H) Multi-touch (PCAP) with Glove / Rain / Stylus modes Wide range of options and accessories for data capture, communication, docking, mounting, power, peripherals and transportation The ideal partner for warehouse, logistics, automotive, outdoor, smart factory, field service etc. Long-term availability

| | |
|---|---|
| **article group specification:** | 2510 |
| **Manufacturer:** | WM |
| **Matchcode manufacturer:** | nein |
| **Manufacturer:** | Winmate |
| **series name:** | Rugged Industrial Tablet PC |
| **Manufacturer item number:** | M101AD |
| **mechanics:** | Rugged Tablet PC |
| **dimensions width:** | 27,15 |
| **dimensions height:** | 19,82 |
| **dimensions depth:** | 2,33 |
| **weight:** | 1,2 |
| **protection device:** | IP65 |
| **colour:** | Schwarz / black |
| **cooling:** | aktiv / fan cooling |
| **Display-diagonal (inch):** | 10,1 |
| **aspect ratio:** | 16:10 |
| **resolution:** | 1920 x 1200 |
| **brightness:** | 800 cd/m² |
| **contrast:** | 800:1 |
| **Display-Technology:** | LCD, LED Backlight |
| **Touch-Screen :** | Projected Capactive / Multi-Touch |

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

| | |
|---|---|
| **usability:** | Finger/ Handschuh/ finger/ glove |
| **CPU Typ:** | Core i5 |
| **CPU Model:** | 1235U |
| **CPU speed:** | 3,3 GHz |
| **CPU cores:** | 10 |
| **RAM size (MB):** | 8192 |
| **RAM max. Größe (MB:** | 32768 |
| **RAM Typ:** | SDRAM-DDR5 |
| **SSD design:** | M.2 |
| **SSD capacity:** | 256 |
| **SSD number:** | 1 |
| **safety:** | TPM 2.0 und Kensington Lock |
| **WLAN:** | Ja / yes |
| **Bluetooth:** | Ja / yes |
| **WWAN:** | Optional / optional |
| **Ethernet_connections:** | 1x RJ-45 |
| **Ethernet data transfer:** | 1 x Gigabit-LAN |
| **Camera front:** | Ja / yes |
| **Camera front resolution:** | 2MP |
| **Camera rear:** | Ja / yes |
| **Camera rear resolution:** | 8MP |
| **Barcode:** | Optional / optional |
| **USB:** | 1x USB 3.0 (Type A), 1x USB 3.0 (Type C) |
| **LAN:** | 1x RJ45 - 10/100/1000 Mbps |
| **Card Slot:** | 1x Micro SDXC Slot, 1x Nano SIM Slot |
| **Audio:** | 1x Audio Combo jack 3.5mm |
| **Power:** | 1x 19 V/DC, DC plug |
| **Docking connector:** | 1x 19-pin Docking Connector |
| **controls:** | 6 Keys: Power, 5x Function |
| **operating system:** | Windows 10 IoT Enterprise |
| **operating temperatur min.:** | -20°C |
| **operating temperatur max.:** | 60°C |
| **Shock:** | MIL-STD-810H Method 516.8 Procedure I |
| **Vibration:** | MIL-STD-810H Method 514.8 Procedure I |
| **Drop:** | MIL-STD-810H Method 516.8, 4 ft |
| **voltage input DC:** | 19 V/DC |
| **external power supply:** | 19 V/DC, 100 - 240 V/AC, DC plug |
| **battery:** | 11.55V 4558 mAh (typ.) Battery (3S2P) |
| **battery Hot-Swap:** | Ja / yes |

## Related links to "M101AD"

- Do you have any questions concerning this product?

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de

- Further products by Winmate

## Available downloads:

Download Drawing Tablet-PC M101AD 250502.pdf

TL Electronic GmbH | Bgm.-Gradl-Str. 1 | 85232 Bergkirchen-Feldgeding

Tel.: +49 (0)8131 33204-0 | Fax: +49 (0)8131 33204-150 | E-Mail: info@tl-electronic.de