


Order number: 15000651

Open text field 2: Embedded Industrie-PC der EmbeddedLine-Serie,
 Intel Core i5-1245UE

Manufacturer: Protech

Weight: 1.65 kg

SE-N108

Price on request

 Prices plus VAT [plus shipping costs](#)

Delivery time: upon request

Product information "SE-N108"

Booksize Embedded PC for professional use Industrial computer in sturdy aluminium housing Designed for industrial applications in continuous operation Easy installation with mounting bars or DIN Rail kit Long-term availability

| | |
|------------------------------|-----------------------|
| article group specification: | 150 |
| Manufacturer: | PT |
| Matchcode manufacturer: | nein |
| Manufacturer: | Protech |
| series name: | EmbeddedLine |
| Manufacturer item number: | SE-N108 |
| mechanics: | Embedded-PC |
| dimensions width: | 21,5 |
| dimensions height: | 5,0 |
| dimensions depth: | 14,26 |
| weight: | 1,65 |
| Material housing: | Aluminium - Magnesium |
| protection device: | IP20 |
| colour: | schwarz / black |
| controls: | 1 Key: Power On/Off |
| VESA-Mounting Interface: | VESA 75 x 75 mm |
| wall mounting: | Ja / yes |
| DIN-Rail: | Ja / yes |
| cooling: | lüfterlos / fanless |
| CPU Typ : | Core i5 |
| CPU Model : | 1245UE |
| CPU 64bit : | Ja |

| | |
|----------------------------|-------------------------------|
| CPU speed: | 3,3 GHz |
| CPU cores: | 10 |
| CPU socket: | FCBGA1744 |
| CPU alternative option 1: | Core i3- 1215UE |
| CPU alternative option 2: | Core i7-1245UE |
| CPU alternative option 3: | Intel Celeron 7305E |
| RAM size (MB): | 8192 |
| RAM max. size (MB): | 32768 |
| RAM Number of benches: | 1 |
| RAM Typ : | SO-DDR5 |
| RAM speed: | 4800 |
| safety: | TPM 2.0 |
| HDD design: | 2.5" |
| HDD max. number: | 1 |
| HDD connection: | SATA 3.0 |
| SSD design: | M.2 |
| SSD max. number: | 1 |
| SSD capacity (GB): | 256 |
| USB : | 2 x USB 2.0 (optional) |
| Audio : | Line-Out, Mic-In |
| Seriell : | 2 x RS-232/422/485 |
| SIM Card Slot : | Ja / yes |
| Display : | 1 x DisplayPort, 1 x HDMI |
| USB : | 4 x USB 3.2 Gen2, 2 x USB 2.0 |
| LAN : | 2x RJ45 - 10/100/1000 Mbps |
| controls: | Power On/Off, Kontroll-LEDs |
| voltage input DC: | 12-24 V/DC |
| voltage input AC: | 100 - 240 V/AC |
| operating temperatur min.: | -20°C |
| operating temperatur min.: | 70°C |
| warranty: | 24 Monate / 24 months |

Related links to "SE-N108"

- [Do you have any questions concerning this product?](#)
- [Further products by Protech](#)